



Coordinates Wall 2

Designed by Michael Anastassiades, 2020




28W - 1402lm - 2700K - CRI> 90

Wall-mounted diffuse lighting device composed of a horizontal bar (model Wall 1) or vertical and horizontal bar (model W2). Each bar is composed of: extruded and processed aluminium body anodized in a champagne or argent colour; diffuser in platinum optical silicone; integrated LED strip (CRI 90). Each model comes with its own rose, whose integrated electronics use only the TRIAC dimmer system.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	805960/035313
Mounting	Wall
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	28
System power (W)	28
Lumen Output (lm)	1402

Physical

Colour	Argent
Length (mm)	100
Net weight (kg)	1
Package height (mm)	145
Package width (mm)	495
Package length (mm)	930
Package volume (m3)	0.07
IP internal	20



Mounting instructions	$\overline{\gamma}$	PDF
Dimmers or chargers	业	PDF

Photometric Files

ULD	<u>.</u>	ZIP
LDT / IES	.4. [DT

Technical Drawings

3D	⊥ ZIP
₿Bim	⊥ ZIP



















https://professional.flos.com/en/global/product/coordinates-wall-2-f1811033/

F1811033

Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Mains Cut Dimming
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**





Replaceable (LED only) light source by a professional



Non-replaceable control gear