



SuperWire T

Designed by Formafantasma, 2024

18W - 1200lm - 2700K - CRI> 90



SuperWire is the first family of modular lamps designed by Formafantasma for Flos. A magical and poetic project, with an essential design but a great stage presence, which recalls the work of the great glass masters of the last century. Made of planar glass and polished aluminum, its design originated from the development of a custom-made light source that emits a warm and homogeneous light. Made up of one or more hexagons of planar glass connected by a polished aluminum element, SuperWire lights up its entire surface thanks to a new source developed by the Flos R&D team: a very thin, flat, soft, flexible LED strip measuring up to one meter, which emits a warm and homogeneous light along its entire length and which can be easily removed for replacement and repair, unique in the panorama of LED bulb-less lamps. This table version, consists of a single module h 45 cm, surmounted by a hexagonal glass cover.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8059607070222	
Mounting	Table	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	Filament LED	
Power (W)	18	
System power (W)	18	
Lumen Output (lm)	1200	

Physical

Colour	Steel
Length (mm)	449
Cord colour	Clear
Cord length (mm)	2000
Net weight (kg)	9
Package volume (m3)	0.2
IP internal	20

	449		_390_
150			
50	297	202	257
390	.: <u>449</u>		

Download

Mounting instructions

业 PDF

Photometric Files

ILD	₹ NTD
DT / IES	<u>↓</u> ZIP

Technical Drawings

2D	⊥ ZIP
3D	₹ ZIP

https://professional.flos.com/en/global/product/superwire-t-d301t01c3eaf2/

D301T01C3EAF2





















Schematic light drawing





,	1	0	
-	2	0	
1	3	0	
\downarrow	4	0	
	5	0	
е			

Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable
Dimming interface	Switch Integrated (Remote Dimmable)
Plug type	Type G, Type A, Type C
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E




Replaceable (LED only) light source by an enduser



Replaceable control gear by an end-user

Spare Parts



01.	Superwire Table diffuser	D301T04A0AASZ
	assembly	
02.	Superwire Table short glass plate	RF301T400
	and bushings	
03.	Superwire Table short glass	RF301T500
	plates and bushings kit 6 pcs	
04.	Superwire Table Led L450	RF301T200
	25MA/42VDC/27K filament	
05.	Superwire Table Led L450	RF301T300
	25MA/42VDC/27K filament kit 6	
	pcs	
06.	Black plug assembly kit & 48V	RF6600130
	driver	
07.	Superwire Kit with special	RF301T100

screws





Superwire Table diffuser assembly







RF301T400

Superwire Table short glass plate and bushings




Superwire Table short glass plates and bushings kit 6 pcs

RF301T200

Superwire Table Led L450 25MA/42VDC/27K filament









F301T300

Superwire Table Led L450 25MA/42VDC/27K filament kit 6 pcs

RF6600130

Black plug assembly kit & 48V driver

RF301T100

Superwire Kit with special screws